

PL-TR-94-2012

AD-A283 272



STOCHASTIC INDEXING

Albert R. Boehm

Hughes STX Corporation
109 Massachusetts Avenue
Lexington, MA 02173

21 January, 1994

Scientific Report No. 1

DTIC
ELECTE
AUG 09 1994
S G D

DTIC QUALITY INSPECTED 5

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

94 8 05 044




PHILLIPS LABORATORY
Directorate of Geophysics
AIR FORCE MATERIEL COMMAND
HANSCOM AIR FORCE BASE, MA 01731-3010

94-24868



"This technical report has been reviewed and is approved for publication"


DONALD D. GRANTAM
Contract Manager
Chief, Atmospheric Structure Branch


ROBERT A. McCLATCHEY
Director, Atmospheric Sciences Division

This report has been reviewed by the ESC Public Affairs Office (PA) and is releasable to the National Technical Information Service (NTIS).

Qualified requestors may obtain additional copies from the Defense Technical Information Center. All others should apply to the National Technical Information Service.

If your address has changed, or if you wish to be removed from the mailing list, or if the addressee is no longer employed by your organization, please notify PL/TSI, Hanscom AFB, MA 01731-3010. This will assist us in maintaining a current mailing list.

Do not return copies of this report unless contractual obligations or notices on a specific document requires that it be returned.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 21 January 1994	3. REPORT TYPE AND DATES COVERED Scientific Report # 1		
4. TITLE AND SUBTITLE STOCHASTIC INDEXING		5. FUNDING NUMBERS F19628-93-C-0051 PE62101F PR6670 TA GS WU AC		
6. AUTHOR(S) Albert R. Boehm				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Hughes STX Corporation 109 Massachusetts Avenue Lexington, MA 02173		8. PERFORMING ORGANIZATION REPORT NUMBER Hughes STX Scientific Report #1		
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Phillips Laboratory 29 Randolph Road Hanscom AFB, MA 01731-3010 Contract Technical Manager: Donald D. Grantham/GPAA		10. SPONSORING / MONITORING AGENCY REPORT NUMBER PL-TR-94-2012		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release: distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A documentation of the computer program for Stochastic Indexing (SED) is presented. A new method of "storing" and retrieving randomly generated features is described.				
14. SUBJECT TERMS Stochastic, clouds, storage, climatology, random numbers, random features, simulation			15. NUMBER OF PAGES 12	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT Unlimited	

CONTENTS

Foreword	1
Purpose	1
Random Number Generators	2
The Demo Program	3
Ith Cloud Spacer	4
Acceptance/Rejection	4
Speed, Networking, and Portability	5
Reference	6
Listing 1	7

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

Foreword

This documentation is from the information file of a computer program, SID, that illustrates the concept of stochastic indexing. This information file is not intended to be a stand-alone report, but to be used with SID to quickly understand a concept that is simple for a programmer to implement but profound to a statistician in its application.

Purpose

The demo program, SID (Stochastic Indexing Demo), in listing 1 simulates clouds as seen by a satellite looking straight down. As a pictorial rendering of clouds, it is rather poor since it only uses circles to indicate where clouds are. But with a little imagination, one can see structures that resemble some types of clouds. By varying the random number seed, the number of clouds, puffs, rows, etc., a wide variety of patterns can be generated.

However, cloud depiction is not its purpose. Its purpose is to demonstrate a new method of "storing" and retrieving randomly generated features. One hundred cloud clusters each with up to 30 puffs (an average of 17) are generated for a total of about 1700 puffs. The location and size of each of these puffs can be retrieved very fast. The computer memory storage required to "store" this information is ZERO!!

Furthermore, the number of puffs could have just as easily been 10 million with additional information on liquid water content, vertical velocity, etc. etc., and the required storage still would be zero. The method is not limited to clouds. The same method could be used for simulated trees in a forest, simulated fish in the sea, or simulated accounts in a bank.

The trick is to reseed the random number generator using the feature's index - in this case the cloud's identification number, 1 to 100. Some background on random number generators may help understanding.

Random Number Generators

Computer random number generators start with some initial number, operate on this number, then return the result as a "random number". Often used is the simple congruential generator:

$$\text{New_random_number} = (\text{Old_random_number} * V1 + V2) \bmod V3$$
where the constants V1, V2, and V3 are carefully chosen to emulate randomness and keep the series of numbers as large as possible before the same number repeats. Thus, these numbers are not random at all but have a definite sequence to them. [Extra Credit Brain Teaser: Given three consecutive random numbers from a simple congruential generator, how can V1, V2, and V3 be calculated?]

Some computers use the video refresh frame number as a `Old_random_number` to obtain varied sequences. I once worked on a

program that used this method only to keep getting the same random sequence. It turned out that at the command RUN, the video refresh frame number was reset to zero and the same Old_random_number was always obtained. Another case I read about used an analog to digital converter hooked up to a Geiger counter reading background random radiation to obtain a "true" random number. The only trouble was that the random numbers had a distinct period in them that coincided with a nearby revolving radar.

In any case, stochastic indexing makes use of these reproducible sequences to rapidly regenerate specific information about each indexed feature such as location, size, etc.

The Demo Program

With regard to the demo program itself, even though it is written in SuperBasic, programmers (FORTRAN, BASIC, etc.) will understand most lines. But a few sections need some additional explanation.

The most important part is the procedure Ith_Cloud. It is used to initially define each cloud's parameters when called from line 230 and is also used to retrieve the ith cloud's parameters when called from line 340.

Ith Cloud Spacer

In Ith_Cloud, line 470 sets the random number seed for the ith cloud. The 99 times the index is a spacer so that the starting number for each cloud is 99 items further along in the random number sequence. Without the 99, the y location of the first cloud would be the x location of the second cloud (sometimes!). A spacer larger than the largest possible number of parameters for each feature keeps the same sequences from being reused. Sometimes too small a spacer causes no noticeable effect; other times, some weird things happen.

Acceptance/Rejection

The algorithm as stated so far will give a uniformly random distribution of clouds. That is, any point is just as likely to have a cloud as any other. There are many simulation algorithms to convert uniform distributions to some desired pattern. The one used here is an acceptance/rejection method that allows stochastic indexing to produce varied patterns.

Lines 480 to 510 contain an acceptance/rejection algorithm which is pretty standard in simulation. It works like this: A function is defined over the area that is close to 1 where you want most clouds, close to zero where you want few clouds, and negative where you want no clouds. The function chosen (feel free to chose your own) here is $\text{COS}(2*\text{PI}*N\text{rows}*(x-y))$ where Nrows

determines the number of cloud rows and (x-y) locates them in lower-left to upper-right orientation. The Cosine function varies from 1 to -1 as x-y varies.

Next a potential site, x and y, is selected. The function at x and y (-1 to 1 in this case) is compared to a random number (0 to 1). If the function is larger than the random number, the site is selected; but if the random number is larger, then the site is rejected and a new pair of x and y is selected. This continues (REPEAT accept_reject) until a site is selected. Do you see why sites with a function near one will have more clouds?

Any function can be used, but make sure it is positive at least in some areas or the REPEAT loop will never be exited. Also functions with small areas of positive values and areas with most values near zero will run very long since most sites will be rejected most of the time.

Speed, Networking, and Portability

Random number generators are generally coded to be very fast. In many cases, a random number can be generated as fast or faster than a number can be fetched from an array in RAM, particularly a multi-dimensional array. If the array must be sent over a LAN (Local Area Network) or WAN (Wide Area Network) for distributed simulation, then stochastic indexing is much faster.

On the other hand, random number generators are often specific to a particular computer. If all computers on the net

are the same, then there is no problem. But if they are different, the random number sequences can be different. There are such things as portable random number generators, but as they say, that is another story.

REFERENCE

Boehm, A., 1994: "Visual Translucent Algorithm, (VISTA)"
Simulation, 62, No.2, 91-97.

LISTING 1

```
100 REMark SID Stochastic Indexing Demo by A.Boehm 30 Aug 1993
110 REMark ***** Set limits. Try varying these. *****
120 Seed=898 :REMark defines a new random set. Try varying
it.
130 Total_clouds=100 :REMark Number of clouds.
140 max_puffs=30 :REMark Max Number of puffs for each cloud
150 max_i_size=10 :REMark max size of cluster, closeness of puffs
160 max_puff_size=2 :REMark max size of puff in cluster
170 Nrows=4 :REMark Number of rows per unit (height of
window) distance
180 :
190 WINDOW 512,246,0,0:WINDOW#2,512,10,0,246:PAPER#2,0:INK#2,5
200 REMark ***** make cloud scape *****
210 MODE 8:PAPER 1:INK 7:CLS
220 FOR i=1 TO Total_clouds
230 Ith_Cloud i:REMark sets x,y,ysize,npuffs_at_i
240 FOR j=1 TO npuffs_at_i
250 CIRCLE x+RND*ysize,y+RND*ysize,RND*max_puff_size
260 END FOR j
270 END FOR i
280 REMark ***** find cloud i, puff j *****
290 REPEAT find
300 CLS#2:PRINT#2, 'Find which cloud? Enter 1 to
';Total_clouds,:INPUT#2, i
310 IF i<1 OR i>Total_clouds THEN BEEP 2000,100:GO TO 300
320 PRINT#2, 'Cloud ';i,'Which puff? Enter 1 to
';npuffs_at_i,:INPUT#2, j
330 IF j<1 OR j>npuffs_at_i THEN BEEP 2000,100:GO TO 320
340 Ith_Cloud i:REMark sets x,y,ysize,npuffs_at_i
350 FOR k=1 TO j-1:a=RND:b=RND:c=RND
360 x= x+RND*ysize:y=y+RND*ysize:r=RND*max_puff_size
370 PRINT #2,'Push s to stop or another key to go on.';
380 REPEAT blink
390 INK 0:CIRCLE x,y,r
400 INK 7:CIRCLE x,y,r
410 a$=INKEY$:IF a$<>' ' THEN EXIT blink
420 END REPEAT blink
430 IF a$=='S' THEN STOP
440 END REPEAT find
450 :
460 DEFine PROCedure Ith_Cloud (i)
470 RANDOMISE i*99+Seed:REMark sets new seed as a function of i
480 REPEAT accept_reject
490 x=RND:y=RND
500 d=COS(2*PI*Nrows*(x-y)):IF d>RND THEN EXIT accept_reject
510 END REPEAT accept_reject
520 x=x*162:y=y*100:REMark scale to fill screen
530 ize=RND*max_i_size
540 npuffs_at_i=RND(5 TO max_puffs)
550 END DEFine Ith_Cloud
```